



SID US Series



PARAMETERS		SPECIFICATIONS
Print Heads		8 print head SII • 510 nozzles • 30 picoliters
Resolution		Up to 720 dpi
Ink	▶ Types	Solvent or eco-solvent
	▶ Colors	Cyan, magenta, yellow, black
	▶ Capacity	Main tanks : 1 liter per color + flush
Media	▶ Max width	3200 mm
	▶ Types	Vinyl, perforated vinyl, polyester, canvas, paper and fabric
	▶ Feeding System	Roll or sheet
Print Speed	▶ Draft	Up to 140 m ² /h
	▶ Standard	Up to 51 m ² /h
	▶ High Quality	Up to 30 m ² /h
Cleaning System		Automatic, with positive pressure system
Cooling System		Pre-heater, front-heater e cooler
Interface		Optical Fiber
Noise level		Printing: < 60 dB Stand by: < 40 dB
Software		Software RIP Standard / PhotoPrint DX
Operating System		Windows 2000 ou XP
Voltage		220 V
Energy Consumption		1400 W (220 CA)
Room Temperature		Temperature 68° ~ 82°F (20° ~ 28°C) Humidity 40% ~ 60%
Equipment Dimension		97 x 475 x 158 cm
Equipment Weight		482 kg



Japanese Original SII print head with automatic voltage control



Well design alloy-aluminum providing resistance and durability



Optical ber cables interface.

• Specifications subject to change without notice

• The speed data can have 5% tolerance on different computers