



SID XCS Series



PARAMETROS	XCS320	
	ESPECIFICACIONES	
Cabezales	510 nozzles • 35 picolitros • 718 mm	
Número de Cabezales	8 cabezales SII	
Resolución	Hasta 720 dpi	
Tinta	<p>▶ Tipos Solvente o eco-solvente</p> <p>▶ Colores Cyan, magenta, yellow and black</p> <p>▶ Capacidad Tanque principal : 5 litros por color + flush</p>	
Midia	<p>▶ Max area de Impresión 3.20 m (126")</p> <p>▶ Sistema de alimentación Rollos o hoja suelta</p> <p>▶ Tipos Vinil, vinil perforado, poliéster, lonas, papel</p>	
Velocidad de impresión	<p>▶ Draft Up to 140 m²/h (1505 sqft/h)</p> <p>▶ Standard Up to 51 m²/h (548 sqft/h)</p> <p>▶ High Quality Up to 30 m²/h (322 sqft/h)</p>	
Sistema de limpieza	Automático, con sistema de presión positiva	
Sistema de secado	Pre-heater, front-heater y ventiladores de enfriamiento	
Interface	Cables de fibra óptica	
Nivel de ruido	Imprimiendo : < 70 dB / Stand by : < 40 dB	
Software	Software RIP Standard / PhotoPrint DX	
Voltaje	AC 220 V, 50 Hz / 60 Hz	
Consumo de energía	1400 W (220 CA)	
Temperatura de operación	Temperatura 68° ~ 75°F (20° ~ 24°C) Humedad 40% ~ 60%	
Dimensiones del equipo	82 x 465 x 130 cm (32" x 182" x 51")	
Dimensiones del empaque	97 x 475 x 158 cm (38" x 187" x 62")	
Peso del equipo	Peso Neto 482 kg (1062 lbs)	Peso Bruto 703 kg (1550 lbs)



Cabezales japoneses originales SII con control automático de voltaje



Estructura en aluminio reforzado



Cables de fibra óptica



Soporte retractable para uso del mouse y teclado



Espacio interno donde colocar el CPU

• Especificaciones sujeto a cambios sin previo aviso

• La velocidad puede variar un 5% en diferentes computadoras



SID XCS Series



PARAMETERS	SPECIFICATIONS
Print Heads	510 nozzles • 35 picoliters • 718 mm print area
Number of print heads	8 print heads SII
Resolution	Up to 720 dpi
Ink ▶ Types	Solvent or eco-solvent
▶ Colors	Cyan, magenta, yellow and black
▶ Capacity	Main tanks : 5 liters per color + flush
Media ▶ Max width	3.20 m (126")
▶ Feeding system	Roll or single sheet
▶ Types	Vinyl, perforated vinyl, polyester, banners, paper or canvas
Print Speed ▶ Draft	Up to 140 m ² /h (1505 sqft/h)
▶ Standard	Up to 51 m ² /h (548 sqft/h)
▶ High Quality	Up to 30 m ² /h (322 sqft/h)
Cleaning system	Automatic, with positive pressure system
Heating and Cooling system	Pre heater, front heater and cooling fans
Interface	Optical Fiber
Noise level	Printing : < 70 dB / Stand by : < 40 dB
Software	Software RIP Standard / PhotoPrint DX
Voltage	AC 220 V, 50 Hz / 60 Hz
Energy consumption	1400 W (220 CA)
Room temperature	Temperature 68° ~ 75°F (20° ~ 24°C) Humidity 40% ~ 60%, non-condensing
Equipment dimension	82 x 465 x 130 cm (32" x 182" x 51")
Shipping dimension	97 x 475 x 158 cm (38" x 187" x 62")
Equipment weight	Net Weight 482 kg (1062 lbs) Gross Weight 703 kg (1550 lbs)



Japanese Original SII print head with automatic voltage control



Well design alloy-aluminum providing resistance and durability



Optical fiber cables interface.



Retractable support for keyboard and mouse



Internal slot for CPU

• Specifications subject to change without notice

• The speed data can have 5% tolerance on different computers