



SID XC Series



PARAMETROS	XC250		XC320	
	ESPECIFICACIONES			
Cabezales	510 nozzles • 35 picolitros • 718 mm			
Número de Cabezales	4 o 6 cabezales SII			
Resolución	Hasta 720 dpi			
Tinta	Solvente o eco-solvente			
▶ Tipos	Solvente o eco-solvente			
▶ Colores	Cyan, magenta, yellow, black, light cyan y light magenta*			
▶ Capacidad	Tanque principal : 5 litros por color + flush			
Midia	▶ Max area de Impresión		▶ Max area de Impresión	
	2.50 m (98")		3.20 m (126")	
	▶ Sistema de alimentación			
	Rollos o hoja suelta			
	▶ Tipos			
	Vinil, vinil perforado, poliéster, lonas, papel			
Velocidad de impresión	▶ Draft		▶ Draft	
	Up to 68 m ² /h (728 sqft/h)		Up to 71 m ² /h (760 sqft/h)	
	▶ Standard		▶ Standard	
	Up to 28 m ² /h (300 sqft/h)		Up to 30 m ² /h (321 sqft/h)	
	▶ High Quality		▶ High Quality	
	Up to 14 m ² /h (150 sqft/h)		Up to 15 m ² /h (160 sqft/h)	
Sistema de limpieza	Automático, con sistema de presión positiva			
Sistema de secado	Pre-heater, front-heater y ventilador de enfriamiento			
Interface	Cables de fibra óptica			
Nivel de ruido	Imprimiendo : < 70 dB / Stand by : < 40 dB			
Software	Software RIP Standard / PhotoPrint DX			
Voltaje	AC 220 V, 50 Hz / 60 Hz			
Consumo de energía	1400 W (220 CA)			
Temperatura de operación	Temperatura 68° ~ 75°F (20° ~ 24°C) Humedad 40% ~ 60%			
Dimensiones del equipo	82 x 390 x 132 cm (32" x 154" x 52")		82 x 465 x 130 cm (32" x 182" x 51")	
Dimensiones del empaque	97 x 405 x 158 cm (38" x 159" x 62")		97 x 475 x 158 cm (38" x 187" x 62")	
Peso del equipo	Peso Neto 400 kg (882 lbs)	Peso Bruto 620 kg (1366 lbs)	Peso Neto 482 kg (1062 lbs)	Peso Bruto 703 kg (1550 lbs)



Cabezales japoneses originales SII con control automático de voltaje



Estructura en aluminio reforzado



Cables de fibra óptica



Soporte retractable para uso del mouse y teclado



Espacio interno donde colocar el CPU

• Especificaciones sujeto a cambios sin previo aviso

• La velocidad puede variar un 5% en diferentes computadoras



SID XC Series



PARAMETERS	SPECIFICATIONS	
	XC250	XC320
Print Heads	510 nozzles • 35 picoliters • 718 mm print area	
Number of print heads	4 or 6 SII print heads	
Resolution	Up to 720 dpi	
Ink ▶ Types	Solvent or eco-solvent	
▶ Colors	Cyan, magenta, yellow, black, light cyan and light magenta *	
▶ Capacity	Main tanks : 5 liters per color + flush	
Media ▶ Max width	2.50 m (98")	3.20 m (126")
▶ Feeding system	Roll or single sheet	
▶ Types	Vinyl, perforated vinyl, polyester, banners, paper or canvas	
Print Speed ▶ Draft	Up to 68 m ² /h (728 sqft/h)	Up to 71 m ² /h (760 sqft/h)
▶ Standard	Up to 28 m ² /h (300 sqft/h)	Up to 30 m ² /h (321 sqft/h)
▶ High Quality	Up to 14 m ² /h (150 sqft/h)	Up to 15 m ² /h (160 sqft/h)
Cleaning system	Automatic, with positive pressure system	
Heating and Cooling system	Pre heater, front heater and cooling fans	
Interface	Optical Fiber	
Noise level	Printing : < 70 dB / Stand by : < 40 dB	
Software	Software RIP Standard / PhotoPrint DX	
Voltage	AC 220 V, 50 Hz / 60 Hz	
Energy consumption	1400 W (220 CA)	
Room temperature	Temperature 68° ~ 75°F (20° ~ 24°C) Humidity 40% ~ 60%, non-condensing	
Equipment dimension	82 x 390 x 132 cm (32" x 154" x 52")	82 x 465 x 130 cm (32" x 182" x 51")
Shipping dimension	97 x 405 x 158 cm (38" x 159" x 62")	97 x 475 x 158 cm (38" x 187" x 62")
Equipment weight	Net Weight 400 kg (882 lbs) Gross Weight 620 kg (1366 lbs)	Net Weight 482 kg (1062 lbs) Gross Weight 703 kg (1550 lbs)



Japanese Original SII print head with automatic voltage control



Well design alloy-aluminum providing resistance and durability



Optical fiber cables interface.



Retractable support for keyboard and mouse



Internal slot for CPU

• Specifications subject to change without notice

• The speed data can have 5% tolerance on different computers